

UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING	DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/644,484	08/20/2003		Trung V. Le	10383US01	7391
·	7590	09/20/2007		EXAM	INER
Attention: Eric D. Levinson Imation Corp.				GETACHEW, ABIY	
Legal Affairs	10			ART UNIT	PAPER NUMBER
P.O. Box 64898 St. Paul, MN 55164-0898			2841		
				. WALL DATE	DELIVERY MODE
				MAIL DATE 09/20/2007	PAPER .

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

		Application No.	Applicant(s)				
Office Action Summers		10/644,484	LE, TRUNG V.				
	Office Action Summary	Examiner	Art Unit				
	ZI 1441 NO DAZE 771	Abiy Getachew	2841				
Period fo	The MAILING DATE of this communication app or Reply	ears on the cover sheet with the c	orrespondence address				
WHIC - Exte after - If NC - Failu Any	ORTENED STATUTORY PERIOD FOR REPLY CHEVER IS LONGER, FROM THE MAILING DATE of time may be available under the provisions of 37 CFR 1.13 SIX (6) MONTHS from the mailing date of this communication. O period for reply is specified above, the maximum statutory period were to reply within the set or extended period for reply will, by statute, reply received by the Office later than three months after the mailing ed patent term adjustment. See 37 CFR 1.704(b).	ATE OF THIS COMMUNICATION 36(a). In no event, however, may a reply be tin will apply and will expire SIX (6) MONTHS from , cause the application to become ABANDONE	N nely filed the mailing date of this communication. D (35 U.S.C. § 133).				
Status							
1)⊠	Responsive to communication(s) filed on 13 Ju	ıly 2007.					
2a) <u></u> ☐	This action is FINAL . 2b)⊠ This action is non-final.						
3) 🗌							
	closed in accordance with the practice under E	Ex parte Quayle, 1935 C.D. 11, 45	53 O.G. 213.				
Disposit	ion of Claims						
4)⊠	4) Claim(s) 1,7-9,11-13,15,19,20,23,25 and 27-30 is/are pending in the application.						
	4a) Of the above claim(s) is/are withdrawn from consideration.						
·	5) Claim(s) is/are allowed.						
	☑ Claim(s) <u>1,7-9,11-13,15,19,20,23,25 and 27-30</u> is/are rejected.						
·	Claim(s) is/are objected to. Claim(s) are subject to restriction and/or	r election requirement					
٥,۵	are subject to restriction and/or	r election requirement.					
Applicati	ion Papers						
9)[The specification is objected to by the Examine	r.					
10)⊠ The drawing(s) filed on <u>20 August 2003</u> is/are: a)⊠ accepted or b)⊡ objected to by the Examiner.							
	Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).						
11)	Replacement drawing sheet(s) including the correct The oath or declaration is objected to by the Ex						
·		diffiler. Note the attached Office	Action of form F 10-132.				
Priority ι	under 35 U.S.C. § 119						
12) Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).							
a) ☐ All b) ☐ Some * c) ☐ None of:							
1. Certified copies of the priority documents have been received.							
 2. Certified copies of the priority documents have been received in Application No. 3. Copies of the certified copies of the priority documents have been received in this National Stage 							
application from the International Bureau (PCT Rule 17.2(a)).							
* See the attached detailed Office action for a list of the certified copies not received.							
Attachmen	it(s)						
1) Notic	ce of References Cited (PTO-892)	4) Interview Summary					
	ce of Draftsperson's Patent Drawing Review (PTO-948) mation Disclosure Statement(s) (PTO/SB/08)	Paper No(s)/Mail Da 5) Notice of Informal P					
	er No(s)/Mail Date 01 01.	6) Other:					

DETAILED ACTION

Continued Examination Under 37 CFR 1.114

A request for continued examination under 37 CFR 1.114, including the fee set forth in 37 CFR 1.17(e), was filed in this application after allowance or after an Office action under *Ex Parte Quayle*, 25 USPQ 74, 453 O.G. 213 (Comm'r Pat. 1935). Since this application is eligible for continued examination under 37 CFR 1.114, and the fee set forth in 37 CFR 1.17(e) has been timely paid, prosecution in this application has been reopened pursuant to 37 CFR 1.114. Applicant's submission *filed on 07/13/2007* has been entered.

Claim Rejections - 35 USC § 102

1. The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless -

- (b) the invention was patented or described in a printed publication in this or a foreign country or in public use or on sale in this country, more than one year prior to the date of application for patent in the United States.
- 2. Claims 1, 7-9, 11-13, 15, 19-20, 23, 25, 27-30 are rejected under 35 U.S.C. 102(b) as being anticipated by Kaneko Yoshio (2002JP-2002-084930 or US2003/0221066).

Regarding claim 1 Kaneko Yoshio discloses, a memory card (See figure 3) comprising: a memory (28, 32); a first connector (25) electrically couple to the memory (28) and conforming to a first connector (25) standard; a second connector (27) electrically coupled to the memory (32) and conforming to a second connector (26), wherein the first connector (25) standard comprises a host computer connector (HCC)

Art Unit: 2841

standard and the second connector (27) standard comprises a device communication connector (DCC) standard; and a controller (29, 35) that controls the memory (28, 32) and controls output via the first connector (25) and the second connector (27), wherein the first (25) and second (27) connectors are electrically coupled to the memory (28, 32) through the controller (29, 35) and wherein the controller (29, 35) comprises a memory controller (30, 34) integrated with a first connector controller (not show) conforming to the first connector (25) standard and integrated with a second connector controller (not show) conforming to the second connector (27) standard, wherein at least one of the first and the second connector comprises a retractable connector (23) that can be positioned in a extended position and a retracted position (See figure 3).

Regarding claims 7,25 Kaneko Yoshio discloses, the memory card (See figures 2-4) wherein, the HCC comprises a standard selected from a group consisting of: a personal computer memory card international association (PCMCIA) standard (see column 3, paragraph 0029 and column 6, paragraph 0066), a PC Card standard, a Card Bus standard (see column 3, paragraph 0029 and column 6, paragraph 0066), a Universal Serial Bus (USB) standard (see column 3, paragraph 0029 and column 6, paragraph 0066), a Universal Serial Bus 2 (USB2) standard (see column 3, paragraph 0029 and column 6, paragraph 0066), an IEEE 1394 Fire Wire standard (see column 3, paragraph 0029 and column 6, paragraph 0066), a Small Computer System Interface (SCSI) standard (see column 3, paragraph 0029 and column 6, paragraph 0029 an

Art Unit: 2841

column 6, paragraph 0066), a Peripheral Component Interconnect (PCI) standard (see column 3, paragraph 0029 and column 6, paragraph 0066), and a conventional serial or parallel standard (see column 3, paragraph 0029 and column 6, paragraph 0066); and the DCC comprises a standard selected from a group consisting of: a Compact Flash standard, a Smart Media standard (see column 3, paragraph 0029 and column 6, paragraph 0066), a Multimedia Card standard (see column 3, paragraph 0029 and column 6, paragraph 0066), a Secure Digital standard (see column 3, paragraph 0029 and column 6, paragraph 0066), a Memory Stick Standard (see column 3, paragraph 0029 and column 6, paragraph 0066), and an xD standard (see column 3, paragraph 0029 and column 6, paragraph 0066).

Regarding claim 8 Kaneko Yoshio discloses the memory card (See figures 2-4) wherein the first connector (explain in claim 1) is disposed (see figure 2) on a different side of the memory card (explained in claim 1) than the second connector (explain in claim 1).

Regarding claim 9 Kaneko Yoshio discloses the memory card (See figures 2-4) wherein the first connector (explain in claim 1) is disposed (see figure 2) on an opposite side of the memory card (explain in claim 1) relative to the second connector (explain in claim 1).

Regard claim 11 Kaneko Yoshio discloses the memory card (See figures 3) further comprising: a housing defining a slot for the retractable connector; and a first electrical contact on the retractable connector and a second electrical contact within the slot, wherein the first electrical contact couples to the second electrical contact when the

Art Unit: 2841

retractable connector is extended from the slot (elements 25, 27 are within the connector 36).

Regarding claim 12 Kaneko Yoshio discloses the memory card (See figure3) wherein the first connector (explain in claim 1) is disposed on the same side of the memory card (25 is on the same side with 28) as the second connector (explain above).

Regarding claim 13 Kaneko Yoshio discloses, the memory card (See figure 3) wherein a set of electrical contact elements of the first connector (explain above) comprise a subset of a set of electrical contact elements (rectangular portion of 25 and 27) of the second connector (explain in claim 1).

Regarding claim 15 Kaneko Yoshio discloses, a memory (28, 32); a first connector (25) electrically coupled to the memory (28, 32) and conforming to a first connector (25) standard; a second connector (27) electrically couple to the memory (32) and conforming to a second connector (27) standard wherein the first connector (25) standard comprises a host computer connector (HCC) standard and the second connector (27) standard comprises a device communication connector (DCC) standard; a first controller (29) electrically coupled to the memory (28) and the first connector (25), the first controller (29) controlling the memory (28) and output via the first connector (25); wherein the first controller (29) comprises a memory controller (30) integrated with a first connector controller (not show) conforming to the first connector (25) standard; and a second controller (35) electrically coupled to the second connector (27) and the first controller (29), the second controller (35) controlling output via the second connector (27) and conforming to the second connector (27) standard, therein the first

Art Unit: 2841

connector (25) is electrically coupled to the memory (28) through the first controller (29), and the second connector (27) is electrically coupled to the memory (32) through the second controller (35) and the first controller (29), wherein at least one of the first and the second connector (27) comprises a retractable connector (23) that can be positioned in a extended position and a retracted position (See figure 3).

Regard claim 19 Kaneko Yoshio discloses the memory card further comprising a third connector (24) electrically coupled to the memory (28) and conforming to a third connector (24) standard.

Regard claim 20 Kaneko Yoshio discloses the memory card further comprising a fourth connector (26) electrically coupled to the memory (32) and conforming to a fourth connector (26) standard.

Regarding claim 23 Kaneko Yoshio discloses, a system (See figure 3) comprising: a first device (21) including a first electrical contact (rectangular portion of 25) for receiving a connector that conform to a first connector (25) standard a second device (22) including a second electrical contact (rectangular portion of 27) for receiving a connector that conforms to a second connector (27) standard; and a memory card (all elements of figure 3) including: a memory (28, 32), a first connector (25) conforming to the first connector (25) standard such that the first connector (25) can be received by the first electrical contact (rectangular portion of 25) of the first device (21), a second connector (26) conforming to the second connector (26) standard such that the second connector (27) can be received by the second electrical contact (rectangular portion of 27) of the second device (22), wherein the first connector (25)

Art Unit: 2841

stand comprises a host. Computer connector (HCC) standard and the second connector (27) standard comprises a device communication connector (DCC) standard, and a controller (29) that controls the memory and controls output via the first connector (25) and the second connector (27) wherein the first (25) and second (27) connectors are electrically coupled to the memory through the controller (29, 35) and wherein the controller (29, 35) comprises a memory controller (30, 34) integrated with a first connector controller (connector not show)conforming to the first connector (25) standard and integrated with a second connector controller (connector not show) conforming to the second connector (27) standard, wherein at least one of the first and the second connector comprises a retractable connector (23) that can be positioned in a extended position and a retracted position (See figure 3).

Regarding claim 27 Kaneko Yoshio discloses, a system (See figure 3) comprising: a first device (21) including a first electrical contact (rectangular portion of 25) for receiving a connector that conforms to a first connector (25) standard; a second device (22) including a second electrical contact (rectangular portion of 27) for receiving a connector that conforms to a second connector (27) standard; and a memory card (21, 22) including: a memory (28, 32), a first connector (25) conforming to the first connector (25) standard such that the first connector (25) can be received by the first electrical contact (rectangular portion of 25) of the first device (21), a second connector (27) conforming to the second connector (27) standard such that the second connector (27) can be received by the second electrical contact (rectangular portion of 27) of the second device (22), wherein the first connector (25) standard comprises a

Art Unit: 2841

host computer connector (HCC) standard and the second connector (27) standard comprises a device communication connector (DCC) standard, a first controller (29) electrically coupled to the memory (28) and the first connector (25), the first controller (29) controlling the memory (28) and output via the first connector (25), wherein the first controller (28) comprises a memory controller (30) integrated with a first connector controller (not show) conforming to the first connector (25) standard, and a second controller (35) electrically coupled to the second connector (27) and the first controller (35), the second controller (35) controlling output via the second connector (27) and conforming to the second connector (27) standard, wherein the first connector (25) is electrically couple to the memory (28) through the first controller (29), and the second connector (27) is electrically couple to the memory (32) through second controller (35) and the first controller (29) wherein at least one of the first and the second connector comprises a retractable connector (23) that can be positioned in a extended position and a retracted position (See figure 3).

Regarding claim 28 Kaneko Yoshio discloses, a memory card (See figure 3) comprising: a memory (28, 32); a first connector (25) electrically couple to the memory (28) and conforming to a first connector (25) standard; a second connector (27) electrically coupled to the memory (32) and conforming to a second connector (26), wherein the first connector (25) standard comprises a host computer connector (HCC) standard and the second connector (27) standard comprises a device communication connector (DCC) standard; one or more controllers that control the memory (28,32) and control output via the first connector and the second connector (25,27), wherein the first

Art Unit: 2841

and second connectors (25,27) are formed along a common side of the memory card (explained in claim 1) and wherein electrical contacts of the second connector (27) comprise a subset of electrical contacts of the first connector(25).

Regarding claim 29 Kaneko Yoshio discloses, wherein the second connector (27) comprises a retractable connector (23) that can be positioned in an extended position and a retracted position. (See figure 3).

Regarding claim 30 Kaneko Yoshio discloses, wherein the electrical contacts of the second connector (27) comprise movable contacts form the second connector (27) when the second connector is in the extended position and wherein the electrical contacts of the second connector (27) comprise a subset of the electrical contacts of the first connector when the second connector is in the retracted position (23). (See figure 3)

Conclusion

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Abiy Getachew whose telephone number is (571) 272 6932. The examiner can normally be reached on Monday to Friday 8Am to 4:30Pm.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Dean A. Reichard can be reached on (571) 272 1984. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Application/Control Number: 10/644,484 Page 10

Art Unit: 2841

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

Abiy Getachew

Examiner

Art Unit 2841

A.G. September 15, 2007

TUAN T. DINH PRIMARY EXAMINER